

GENERAL SPECIFICATIONS

	Material	Body	10 mm acrylic top lid on 304-grade stainless steel body (opt. 316 grade), 6 mm acrylic side panels (opt. tempered glass).	
		Wing	Tempered glass.	
	Available for	INDOOR/OUTDOOR <input type="checkbox"/>		INDOOR <input checked="" type="checkbox"/>
	Energy	110/220-240V 50-60Hz. AC (±%10) - 24V DC		
	Control System	Dry contact (ground control)		
	Nr. of Passage Lanes	Double Unit		Single Unit
			<input checked="" type="checkbox"/>	
	Wing Movement	Wings Retracting Into Body		90° (Wing) Rotor System
			<input type="checkbox"/>	
	Operation	BI-DIRECTIONAL <input checked="" type="checkbox"/>		UNI-DIRECTIONAL <input type="checkbox"/>
	Indicators		STANDARD <input type="checkbox"/>	OPTIONAL <input checked="" type="checkbox"/>
			STANDARD <input checked="" type="checkbox"/>	OPTIONAL <input type="checkbox"/>
	Emergency	Wings allow free passage		
	Reduced Mobility (ADA) Compatibility	AVAILABLE <input checked="" type="checkbox"/>		NOT AVAILABLE <input type="checkbox"/>